



Attestation of Compliance

Reference No. : LCSB01014008E

Applicant : SUNSHINE LED LIMITED

Address : 3F, B Building, DaTian Printing Factory, 5th Industrial Area,
TianLiao Village, GongMing Town, Bao'an District, Shenzhen,
China

Trade Mark : N/A

Product : Led strip light

Model(s) : SEE ANNEX I

Tested according to : EN IEC 55015:2019+A11:2020
EN IEC 61547:2023

The submitted products have been tested by us with the listed standards.

This Attestation of Compliance is issued according to the council Directive 2014/30/EU, Referred to as the Electromagnetic Compatibility. It confirms that the listed product complies with all essential requirements of the EMC directive and applies only to the sample and its technical documentation submitted to Shenzhen Southern LCS Compliance Testing Laboratory Ltd. for testing.

After preparation of the necessary technical documentation as well as the EC conformity declaration the required CE marking can be affixed on the product. Other relevant Directives have to be observed.



Date of issue: March 19, 2024

Manager



ANNEX I:



Reference No. : LCSB01014008E

Model(s) :

Model	Rating
SU-LR3528WNWWW240/WPC/YPD-24	24VDC, 19.2W/m, Max. 1m, Max. 19.2W, tc: 85°C
SU-LR3528WNWWW120/WPC/YPD-24/12	24V/12VDC, 9.6W/m, Max. 1m, Max. 9.6W, tc: 85°C
SU-LR3528WNWWW60/WPC/YPD-24/12	24V/12VDC, 4.8W/m, Max. 1m, Max. 4.8W, tc: 85°C
SU-LR5050WNWWW30/WPC/YPD-12/24	24V/12VDC, 7.2W/m, Max. 1m, Max. 7.2W, tc: 85°C
SU-HLR5050WNWWW60/WPC/YPD-12/24	24V/12VDC, 14.4W/m, Max. 1m, Max. 14.4W, tc: 85°C
SU-LR5050RGB30/WPC/YPD-12/24	24V/12VDC, 7.2W/m, Max. 1m, Max. 7.2W, tc: 85°C
SU-LR5050RGB60/WPC/YPD-12/24	24V/12VDC, 14.4W/m, Max. 1m, Max. 14.4W, tc: 85°C
SU-LR5050RGBW/NW/WW60/WPC/YPD-24	24VDC, 19.2W/m, Max. 1m, Max. 19.2W, tc: 85°C
SU-HLR5050CCT60/WPC/YPD-24	24V/12VDC, 14.4W/m, Max. 1m, Max. 14.4W, tc: 85°C
SU-LR3014WNWWW60/WPC/YPD-12/24	24V/12VDC, 7.2W/m, Max. 1m, Max. 7.2W, tc: 85°C
SU-LR3014WNWWW120/WPC/YPD-12/24	24V/12VDC, 14.4W/m, Max. 1m, Max. 14.4W, tc: 85°C
SU-LR2835BD/WNWWW60/WPC/YPD-12/24	24V/12VDC, 7.2W/m, Max. 1m, Max. 7.2W, tc: 85°C
SU-LR5050-RGB3K/4K6K4C60/WPC/YPD-24	24VDC, 19.2W/m, Max. 1m, Max. 19.2W, tc: 85°C
SU-LR2835WNWWW60/WPC/YPD-12/24	24V/12VDC, 7.2W/m, Max. 1m, Max. 7.2W, tc: 85°C
SU-LR2835WNWWW120/WPC/YPD-12/24	24V/12VDC, 14.4W/m, Max. 1m, Max. 14.4W, tc: 85°C

